

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

ATTORNEY'S DOCKET NUMBER

P21917

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

10/030124

INTERNATIONAL APPLICATION NO.

PCT/JP00/04003

INTERNATIONAL FILING DATE

19 June 2000

PRIORITY DATE CLAIMED

18 August 1999

TITLE OF INVENTION

METHOD OF PURIFYING ORGANIC PHOSPHORIC ESTER

APPLICANT(S) FOR DO/EO/US

Kiyoharu HIRAO and Masasuke ODA

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information.

1. ☒ This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to promptly begin national examination procedures (35 U.S.C. 371(f)).
4. ☒ The US has been elected by the expiration of 19 months from the priority date (PCT Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☒ is attached hereto (required only if not communicated by the International Bureau).
 - b. ☒ has been communicated by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ An English language translation of the International Application as filed (35 U.S.C. 371 (c)(2)).
7. Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
 - b. ☐ have been communicated by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3))
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
"Executed"
10. ☐ An English language translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (U.S.C. 371(c)(5)).

Items 11 to 16 below concern other document(s) or information included:

11. ☒ Assignee: DAIHACHI CHEMICAL INDUSTRY CO., LTD. of Osaka, JAPAN
12. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
13. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
14. ☒ A FIRST preliminary amendment.
☐ A SECOND or SUBSEQUENT preliminary amendment.
15. ☐ A substitute specification.
16. ☐ A change of power of attorney and/or address letter.
17. ☐ Figure of Drawing to be published
18. ☒ Other items or information:
Cover Sheet and International Application as published in Japanese.
PCT/IPEA/409(in Japanese).
PCT/RO/101-PCT Request(in Japanese).
PCT/ISA/210(in Japanese and English).
PCT/IB/308
Executed Small Entity Status Form.
Claim of Priority.

U.S. APPLICATION NO. (if known, see 37 CFR 1.5)

10/030124

INTERNATIONAL APPLICATION NO.

PCT/JP00/04003

531 Rec'd PCT

24 JAN 2002

ATTORNEY'S SECRET NUMBER

P21917

19. ☒ The following fees are submitted:

Basic National Fee (37 CFR 1.492(a)(1)-(5)):

Search report has been prepared by the EPO or JPO. \$ 890.00

International preliminary examination fee paid to USPTO (37 CFR 1.482). \$ 710.00

No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)). \$ 740.00

Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO. \$1,040.00

International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4). \$ 100.00

ENTER APPROPRIATE BASIC FEE AMOUNT =

CALCULATIONS

PTO USE ONLY

\$890.00

Surcharge of \$130.00 for furnishing the oath or declaration later than 20 30 months from the earliest claimed priority date (37 CFR 1.492(e)).

\$

Claims	Number Filed	Number Extra	RATE		
Total Claims	13 - 20 =	0	X \$18.00	\$0.00	
Independent Claims	1 - 3 =	0	X \$84.00	\$0.00	

Multiple dependent claim(s) (if applicable)

+ \$280.00

\$0.00

TOTAL OF ABOVE CALCULATIONS =

\$890.00

☒ Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by $\frac{1}{2}$.

\$445.00

SUBTOTAL =

\$445.00

Processing fee of \$130.00 for furnishing the English translation later than 20 30 months from the earliest claimed priority date (37 CFR 1.492(f)).

+

Extension of Time fee in the amount of \$

TOTAL NATIONAL FEE =

\$445.00

Fee for recording the enclosed assignment (37 CFR 1.21(h). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property

+

40.00

TOTAL FEES ENCLOSED =

\$485.00

Amount to be refunded

\$

Charged

\$

a. ☒ A check in the amount of \$485.00 to cover the above fees is enclosed.b. ☐ Please charge my Deposit Account No. in the amount of \$ to cover the above fees.c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 19-0089.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO CUSTOMER NO. 7055

AT THE PRESENT ADDRESS OF:

Bruce H. Bernstein
GREENBLUM & BERNSTEIN, P.L.C.
1941 Roland Clarke Place
Reston, VA 20191
(703) 716-1191

07055

PATENT TRADEMARK OFFICE

SIGNATURE
Bruce H. Bernstein
NAME

33,329

29,027
REGISTRATION NUMBER

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Kiyoharu HIRAO et al.

Serial No : Not Yet Assigned (National Phase of PCT/JP00/04003)

Filed : Concurrently Herewith (International Filing Date June 19, 2000)

For : METHOD OF PURIFYING ORGANIC PHOSPHORIC ESTER

PRELIMINARY AMENDMENT

Commissioner of Patents and Trademarks
Washington, D.C. 20231

Sir:

Prior to the examination of the above-identified patent application on the merits, the Examiner is respectfully requested to amend the claims as follows:


IN THE CLAIMS

Please amend the claims as follows (a marked-up copy of the claim amendments is provided as an attachment to this Amendment):

3. (Amended-Clean Text) A method according to claim 1, wherein the ratio between the crude organic phosphoric ester and the epoxy compound is 1:1 to 1:20 (molar ratio) based on an acid value of the crude organic phosphoric ester.
4. (Amended-Clean Text) A method according to claim 1, wherein the treatment with the epoxy compound is carried out at 40 to 160°C.

5. (Amended-Clean Text) A method according to claim 1, wherein the organic phosphoric ester that has been treated with the epoxy compound is treated with water or an acidic aqueous solution in advance of the treatment with the alkaline aqueous solution.
6. (Amended-Clean Text) A method according to claim 1, wherein the alkaline aqueous solution is an aqueous solution of an alkali metal carbonate.
8. (Amended-Clean Text) A method according to claim 1, wherein an amount of an alkali compound in the alkaline aqueous solution is 0.1 to 50 molar equivalent with respect to the acid value of the crude organic phosphoric ester which is not yet treated with the epoxy compound.
9. (Amended-Clean Text) A method according to claim 1, wherein a concentration of the alkaline aqueous solution is 0.01 to 10 wt%.
10. (Amended-Clean Text) A method according to claim 1, wherein the treatment with the alkaline aqueous solution is carried out at 60 to 120°C.

11. (Amended-Clean Text) A method according to claim 1, wherein the organic phosphoric ester is a compound represented by the general formula (II):



wherein Q^1 , Q^2 , Q^3 and Q^4 , the same or different, are an alkyl group having a carbon number of 1 to 6, R^6 , R^7 , R^8 and R^9 are methyl groups, m^1 , m^2 , m^3 and m^4 , the same or different, are an integer of 1 to 3, n^1 and n^2 , the same or different, are an integer of 0 to 2, and x is an integer of 0 to 5.

12. (Amended-Clean Text) A method according to claim 1, wherein the crude organic phosphoric ester is dehydrated in advance of the treatment with the epoxy compound.


13. (Amended-Clean Text) A method according to claim 1, wherein the organic phosphoric ester that has been treated with the alkaline aqueous solution is washed with water and subjected to steam distillation.

REMARKS

By the above amendment, the claims have been amended to delete multiple dependency.

If there should be any questions, the Examiner is invited to contact the undersigned at the telephone number listed below.

Respectfully submitted,
Kiyoharu HIRAO et al.


Bruce H. Bernstein
Reg. No. 29,027

January 23, 2001
GREENBLUM & BERNSTEIN, P.L.C.
1941 Roland Clarke Place
Reston, VA 20191
(703) 716-1191


MARKED-UP COPY OF AMENDED CLAIMS

3. (Amended) A method according to claim 1 [or 2], wherein the ratio between the crude organic phosphoric ester and the epoxy compound is 1:1 to 1:20 (molar ratio) based on an acid value of the crude organic phosphoric ester.
4. (Amended) A method according to claim 1 [any one of claims 1 to 3], wherein the treatment with the epoxy compound is carried out at 40 to 160°C.
5. (Amended) A method according to claim 1 [any one of claims 1 to 4], wherein the organic phosphoric ester that has been treated with the epoxy compound is treated with water or an acidic aqueous solution in advance of the treatment with the alkaline aqueous solution.
6. (Amended) A method according to claim 1 [any one of claims 1 to 5], wherein the alkaline aqueous solution is an aqueous solution of an alkali metal carbonate.
8. (Amended) A method according to claim 1 [any one of claims 1 to 7], wherein an amount of an alkali compound in the alkaline aqueous solution is 0.1 to 50 molar equivalent with respect to the acid value of the crude organic phosphoric ester which is not yet treated with the epoxy compound.

9. (Amended) A method according to claim 1 [any one of claims 1 to 8], wherein a concentration of the alkaline aqueous solution is 0.01 to 10 wt%.

10. (Amended) A method according to claim 1 [any one of claims 1 to 9], wherein the treatment with the alkaline aqueous solution is carried out at 60 to 120°C.

11. (Amended) A method according to claim 1 [any one of claims 1 to 10], wherein the organic phosphoric ester is a compound represented by the general formula (II):



wherein Q^1 , Q^2 , Q^3 and Q^4 , the same or different, are an alkyl group having a carbon number of 1 to 6, R^6 , R^7 , R^8 and R^9 are methyl groups, m^1 , m^2 , m^3 and m^4 , the same or different, are an integer of 1 to 3, n^1 and n^2 , the same or different, are an integer of 0 to 2, and x is an integer of 0 to 5.

12. (Amended) A method according to claim 1 [any one of claims 1 to 11], wherein the crude organic phosphoric ester is dehydrated in advance of the treatment with the epoxy compound.

13. (Amended) A method according to claim 1 [any one of claims 1 to 12], wherein the organic phosphoric ester that has been treated with the alkaline aqueous solution is washed with water and subjected to steam distillation.

DESCRIPTION

Method of Purifying Organic Phosphoric Ester

Technical Field

5 The present invention relates to a method of purifying
an organic phosphoric ester which is useful as a plasticizer or a
flame retardant for a synthetic resin. More particularly, it
relates to a purification method for obtaining an organic
phosphoric ester which has a low acid value and is excellent in
10 heat resistance, storage stability and hydrolytic resistance.

Background Art

Organic phosphoric esters are synthesized by a method
for reacting phosphorus oxychloride with an alcohol or phenol
15 under dehydrochlorination, or the like. However, since it is
difficult to complete the esterification by this synthesis method,
the synthesized organic phosphoric esters show some acid value
due to phosphoric acid and chloride derived from the starting
materials.

20 Since the substances that generate the acid value have
a bad influence on physical properties such as heat resistance,
hydrolytic resistance and storage stability of the organic
phosphoric esters, crude organic phosphoric esters are purified
to remove the substances generating the acid value, thereby
25 reducing the acid value of the organic phosphoric esters. The

purification treatment may be carried out by neutralization using a basic substance, e.g., by wet neutralization using alkali metal hydroxide such as sodium hydroxide or dry neutralization using an alkali earth metal compound such as calcium carbonate and magnesium hydroxide, followed by washing with water, or by distillation.

However, in the case where a highly viscous organic phosphoric ester is subjected to the wet neutralization using alkali metal hydroxide, separation of an aqueous phase and an oily phase is not performed well and takes time. Moreover, there is a problem in that a relatively large amount (e.g., several tens to hundreds of ppm) of alkali metal remains in the separated oily phase. The remaining alkali metal is not preferable because it causes a bad influence on the heat resistance and the hydrolytic resistance of the organic phosphoric ester.

In order to reduce the amount of alkali metal remaining in the organic phosphoric ester, there has been proposed a method of diluting the highly viscous organic phosphoric ester with an organic solvent to reduce the viscosity or a method of salting-out the highly viscous organic phosphoric ester, thereby facilitating the separation of the aqueous phase and the oily phase. However, even in these methods, the alkali metal cannot be eliminated completely and washing with water needs to be carried out many times to get rid of the yet remaining alkali

metal. The problem of the remaining alkali metal is also involved in the dry neutralization.

With respect to some organic phosphoric esters, the whole mixture including the crude organic phosphoric ester may
5 be emulsified during the wet neutralization using alkali metal hydroxide, so that the aqueous phase and the oily phase may not be separated well.

In the case of purification by distillation, low molecular weight organic phosphoric esters are purified without suffering
10 from the above-described problem of the remaining alkali metal. However, it is difficult to conduct the purification treatment itself for high molecular weight organic phosphoric esters.

There are other impurities than the alkali metal causing a bad influence on the physical properties such as heat
15 resistance, hydrolytic resistance and storage stability of the organic phosphoric ester. Examples of such impurities include unreacted compounds in which the esterification is not completed, compounds in which phosphoric acid or alcohols and a reaction catalyst are combined and other impurities in a small
20 amount derived from the starting materials.

To eliminate these impurities, only the above-described purification treatment by neutralization or distillation is insufficient and a purification apparatus of high fractionation efficiency is required. However, there is a problem in that the
25 apparatus is expensive and reduces the product yield, thereby

increasing the cost.

To solve the problem, there has been developed a purification method of the organic phosphoric ester by treating a crude organic phosphoric ester with an epoxy compound, 5
subjecting the resulting product to thermal treatment in the presence of water, washing the obtained product with water, and then removing residual water (see Japanese Unexamined Patent Publication No. Hei 8(1996)-67685).

According to the method, impurities in the organic 10
phosphoric ester are reacted with the epoxy compound, the reaction product is hydrolyzed in water to convert into a water-soluble compound and the obtained water-soluble compound is removed by washing with water, thereby removing the impurities in the organic phosphoric ester. In this method, it is important 15
to selectively hydrolyze only the compound obtained by the reaction with the epoxy compound. If the hydrolysis is insufficient, the acid value of the organic phosphoric ester cannot be reduced. To the contrary, if the hydrolysis is carried out excessively, the organic phosphoric ester itself to be purified 20
is also hydrolyzed.

Accordingly, in order to purify the organic phosphoric ester efficiently by the above-described method, it is necessary to set the optimum conditions such that the organic phosphoric ester itself is not hydrolyzed during the thermal treatment. The 25
optimum conditions must be established in view of a kind and

amount of the organic phosphoric ester, a kind of the epoxy compound, conditions of the thermal treatment (e.g., temperature, time, water amount and the like), as well as an apparatus used, which requires complicated work. Especially, in the case of purifying a large quantity of the organic phosphoric ester in an industry scale, there has been a problem in that the treatment conditions are difficult to establish and thus the acid value of the organic phosphoric ester cannot be reduced sufficiently.

Disclosure of Invention


To solve the above-mentioned problems, the present invention is intended to provide a method of purifying an organic phosphoric ester for stably obtaining the organic phosphoric ester having a low acid value and being excellent in heat resistance, hydrolytic resistance and storage stability, the method being free from the influence by the kind and amount of the organic phosphoric ester as well as the treatment conditions.

According to the present invention, provided is a method of purifying an organic phosphoric ester characterized in that the purification is carried out by treating a crude organic phosphoric ester with an epoxy compound and treating the treated organic phosphoric ester with an alkaline aqueous solution.

Best Mode for Carrying out the Invention

The organic phosphoric esters to be treated by the method of the present invention are compounds that are known in the art and generally used as a plasticizer and/or a flame retardant for a resin. However, they are not particularly limited as long as they contain impurities generated through the synthesis thereof.

The organic phosphoric esters are represented by the general formula (I):




wherein n is an integer of 0 to 30, R^1 , R^2 , R^3 and R^4 , the same or different, are an aliphatic hydrocarbon residue or an aromatic hydrocarbon residue when n is 0 or an aromatic hydrocarbon residue when n is 1 to 30, and R^5 is a bivalent organic group.

The aliphatic hydrocarbon residue represented by R^1 , R^2 , R^3 and R^4 in the general formula (I) may preferably be a straight-chain or branched-chain alkyl group having a carbon number of 8 to 18. Examples thereof include 2-ethylhexyl, n -octyl, sec -octyl, decyl, dodecyl, hexadecyl, octadecyl and the like.

The aromatic hydrocarbon residue may preferably be an

aryl group having a carbon number of 6 to 15. Examples thereof include phenyl, cresyl, xylyl, 2,6-dimethylphenyl, 2,4,6-trimethylphenyl, butylphenyl, nonylphenyl and the like.

The bivalent organic group of R^5 may be an alkylene group, an arylene group or the like. Examples thereof include an alkylene group such as methylene, ethylene, trimethylene, propylene, tetramethylene and ethylethylene, an arylene group such as (o-, m- or p-)phenylene, and the following groups:



Examples of the organic phosphoric ester compounds of the general formula (I) include not only monomers but also polymers such as dimers and trimers. The organic phosphoric ester to be treated by the method of the present invention may be a simple compound thereof, or a mixture thereof.

The organic phosphoric esters (I) are roughly classified into the organic phosphoric esters having no aromatic hydrocarbon residues and those having aromatic hydrocarbon residues.

Examples of the organic phosphoric esters having no aromatic hydrocarbon residues include trimethyl phosphate,

triethyl phosphate, tri-n-propyl phosphate, triisopropyl phosphate, tri(2-ethylhexyl)phosphate, tridecyl phosphate, trioctadecyl phosphate, tris(tribromoneopentyl)phosphate, tris(trichloroneopentyl)phosphate and the like.

5 Examples of the organic phosphoric esters having aromatic hydrocarbon residues include monomers of organic phosphoric esters such as triphenyl phosphate, [tri(o-, m- or p-)chlorophenyl]phosphate, [tri(o-, m- or p-)bromophenyl] phosphate, [tri(o-, m- or p-)methylphenyl]phosphate, [tri(o-, m- or p-)ethylphenyl]phosphate, [tri(o-, m- or p-)n-propylphenyl] phosphate, [tri(o-, m- or p-)isopropylphenyl]phosphate, [tri(o-, m- or p-)n-butylphenyl]phosphate, [tri(o-, m- or p-)sec-butylphenyl]phosphate, [tri(o-, m- or p-)tert-butylphenyl]phosphate, [tri(o-, m- or p-)octylphenyl] phosphate, [tri(o-, m- or p-)nonylphenyl]phosphate,

10

15

 tris[(2,3-, 2,4-, 2,5-, 2,6-, 3,4- or 3,5-)dimethylphenyl] phosphate, tris[(2,3-, 2,4-, 2,5-, 2,6-, 3,4- or 3,5-)diethylphenyl]phosphate, tris[(2,3-, 2,4-, 2,5-, 2,6-, 3,4- or 3,5-)di-n-propylphenyl]phosphate, tris[(2,3-, 2,4-, 2,5-, 2,6-, 3,4- or 3,5-)diisopropylphenyl]phosphate, tris[(2,3-, 2,4-, 2,5-, 2,6-, 3,4- or 3,5-)di-n-butylphenyl]phosphate, tris[(2,3-, 2,4-, 2,5-, 2,6-, 3,4- or 3,5-)di-sec-butylphenyl]phosphate, tris[(2,3-, 2,4-, 2,5-, 2,6-, 3,4- or 3,5-)di-tert-butylphenyl]phosphate,

20

 tris[(2,3,6-, 2,3,4-, 2,4,6- or 3,4,5-)trimethylphenyl] phosphate, tris[(2,3,6-, 2,3,4-, 2,4,6- or 3,4,5-)triethylphenyl]

25

phosphate, tris[(2,3,6-, 2,3,4-, 2,4,6- or 3,4,5-)tripropylphenyl]
phosphate, cresyldiphenyl phosphate and the like, and

condensates thereof such as alkylenebis[di(o-, m- or
p-)phenyl phosphate], alkylenebis[di(o-, m- or p-)methylphenyl
5 phosphate], resorcinbis[di(o-, m- or p-)phenyl phosphate],
resorcinbis[di(o-, m- or p-)methylphenyl phosphate],
resorcinbis[di(o-, m- or p-)ethylphenyl phosphate],
resorcinbis[bis(2,3-, 2,4-, 2,5-, 2,6-, 3,4- or 3,5-)dimethylphenyl
phosphate], hydroquinonebis[di(o-, m- or p-)phenyl phosphate],
10 hydroquinonebis[di(o-, m- or p-)methylphenyl phosphate],
hydroquinonebis[di(o-, m- or p-)ethylphenyl phosphate],
hydroquinonebis[bis(2,3-, 2,4-, 2,5-, 2,6-, 3,4- or
3,5-)dimethylphenyl phosphate], bis[di(o-, m- or p-)phenyl
phosphate]bisphenol A, bis[di(o-, m- or p-)methylphenyl
15 phosphate]bisphenol A, bis[di(o-, m- or p-)ethylphenyl
phosphate]bisphenol A, bis[bis(2,3-, 2,4-, 2,5-, 2,6-, 3,4- or
3,5-)dimethylphenyl phosphate]bisphenol A and the like.

The crude organic phosphoric esters to be treated by
the method according to the present invention include
20 impurities generated through the synthesis thereof. Examples
of the impurities include alkali metal compounds and Lewis acid
compounds that are used as a reaction catalyst, compounds
having metal derived from the reaction catalyst (metal in the
reaction catalyst) bonded to one of bonds of phosphoric acid,
25 dimers formed by combining phosphoric diesters via metal in the

reaction catalyst, compounds formed by combining phosphoric acid as a starting compound and the reaction catalyst, compounds formed by combining alcohols or phenols with the reaction catalyst, unreacted compounds in which esterification
5 is not completed (compounds having P-Cl bond) and the like. In the present invention, these compounds are generally called as "impurities".

The purification method according to the present invention is intended to efficiently remove these impurities.

10 The organic phosphoric esters to be treated are referred to as "crude organic phosphoric esters" to imply that they include the impurities.

The organic phosphoric esters are obtained by a method known in the art. In general, they are obtained by reacting
15 phosphorus oxychloride with appropriate alcohols or phenols under noncatalytic condition or in the presence of a Lewis acid catalyst (e.g., aluminum chloride, magnesium chloride or titanium tetrachloride).

For example, an aromatic bisphosphate is obtained by
20 reacting phosphorus oxychloride with an aromatic monohydroxy compound (monovalent phenol) in the presence of a Lewis acid catalyst and reacting the obtained diaryl phosphorohalidate with an aromatic dihydroxy compound (bivalent phenol) in the presence of the above-described catalyst (e.g., see Japanese
25 Unexamined Patent Publication No. Hei 5(1993)-1079).

The aromatic bisphosphate is obtained also by reacting phosphorus oxychloride with an aromatic dihydroxy compound, removing unreacted phosphorus oxychloride, and then reacting the resulting product with an aromatic monohydroxy compound
5 (see Japanese Unexamined Patent Publication No. Sho 63(1988)-227632).

Further, the aromatic bisphosphate is obtained also by reacting phosphorus oxychloride with a mixture of an aromatic monohydroxy compound and an aromatic dihydroxy compound.

10 Examples of phenols used in the above-described manufacture of the organic phosphoric esters include monovalent phenols such as phenol, (o-, m- or p-)methylphenol, (2,3-, 2,4-, 2,5-, 2,6-, 3,4- or 3,5-)dimethylphenol and the like, and bivalent phenols such as resorcin, hydroquinone, bisphenol
15 A, bisphenol F, bisphenol S, biphenol, naphthol and the like.

In the manufacture of the organic phosphoric esters, reaction conditions such as an amount of the reaction catalyst, the ratio between phosphoric acid and alcohols or phenols, the ratio between phosphorus oxychloride and alcohols or phenols,
20 reaction temperature, reaction time and the like are appropriately established.

The thus manufactured organic phosphoric esters generally contain a large amount of impurities. However, according to the purification method of the present invention,
25 the impurities are efficiently removed from the crude organic

Variable	Mean	SD	Min	Max
Age	34.5	10.5	18	65
Gender	50%	50%	Male	Female
Marital Status	65%	35%	Married	Single
Education	12.5	1.5	9	16
Income	3500	1500	1000	8000
Occupation	30%	70%	Professional	Non-Professional
Religion	60%	40%	Hindu	Muslim
Health Status	75%	25%	Good	Poor
Smoking Status	40%	60%	Smoker	Non-Smoker
Alcohol Consumption	30%	70%	Regular	Occasional
Stress Level	65%	35%	Low	High
Sleep Pattern	70%	30%	Regular	Irregular
Dietary Habits	60%	40%	Vegetarian	Non-Vegetarian
Exercise Frequency	50%	50%	Regular	Irregular
Family Size	3.5	1.5	1	6
Urban/Rural	70%	30%	Urban	Rural
Health Insurance	80%	20%	Yes	No
Medical History	10%	90%	Chronic	Acute
Genetic Factors	5%	95%	Present	Absent
Environmental Factors	30%	70%	High	Low
Lifestyle Changes	45%	55%	Adopted	Not Adopted
Healthcare Access	90%	10%	Good	Poor
Healthcare Costs	1500	500	500	3000
Healthcare Satisfaction	70%	30%	Satisfied	Dissatisfied
Healthcare Utilization	60%	40%	Regular	Irregular
Healthcare Quality	85%	15%	High	Low
Healthcare Accessibility	95%	5%	Good	Poor
Healthcare Affordability	80%	20%	Yes	No
Healthcare Effectiveness	90%	10%	High	Low
Healthcare Safety	98%	2%	Yes	No
Healthcare Transparency	85%	15%	High	Low
Healthcare Accountability	92%	8%	Yes	No
Healthcare Innovation	75%	25%	High	Low
Healthcare Research	80%	20%	Yes	No
Healthcare Education	85%	15%	High	Low
Healthcare Training	90%	10%	Yes	No
Healthcare Certification	95%	5%	Yes	No
Healthcare Accreditation	98%	2%	Yes	No
Healthcare Regulation	99%	1%	Yes	No
Healthcare Monitoring	99%	1%	Yes	No
Healthcare Evaluation	99%	1%	Yes	No
Healthcare Improvement	99%	1%	Yes	No
Healthcare Innovation	99%	1%	Yes	No
Healthcare Research	99%	1%	Yes	No
Healthcare Education	99%	1%	Yes	No
Healthcare Training	99%	1%	Yes	No
Healthcare Certification	99%	1%	Yes	No
Healthcare Accreditation	99%	1%	Yes	No
Healthcare Regulation	99%	1%	Yes	No
Healthcare Monitoring	99%	1%	Yes	No
Healthcare Evaluation	99%	1%	Yes	No
Healthcare Improvement	99%	1%	Yes	No

5



10

15

20

formula (II), particular examples to which the present invention is suitably applied are bis(diphenyl phosphate) bisphenol A, bis[di(o-, m- or p-)methylphenyl phosphate]bisphenol A, bis[di(o-, m- or p-)ethylphenyl phosphate]bisphenol A and
5 bis[bis(2,3-, 2,4-, 2,5-, 2,6-, 3,4- or 3,5-)dimethylphenyl phosphate]bisphenol A.

The crude organic phosphoric esters to be treated include solid ones and liquid ones. The purification method of the present invention can be applied to either form. However,
10 the liquid ones are preferable in view of easy handling.

Where a solid organic phosphoric ester or a highly viscous liquid organic phosphoric ester is used, it is preferred to dissolve the solid or liquid organic phosphoric ester in a solvent before applying the method of the present invention thereto.

15 The solvent used in this case is not particularly limited as long as it is able to dissolve the organic phosphoric ester and does not inhibit the action of an epoxy compound to be inferred in the later description. Specific examples thereof include aromatic solvents such as toluene, xylene and dichlorobenzene,
20 aliphatic solvents such as hexane, heptane and cyclohexane.

Where the above-described solvent is used in the synthesis of the organic phosphoric ester, the method of the present invention can be applied without separating the solvent and the organic phosphoric ester. Even if the solvent is separated and
25 left in the organic phosphoric ester, the purification method of

the present invention is not hindered.

According to the purification method of the present invention, first, the crude organic phosphoric ester is treated with an epoxy compound (hereinafter referred to as "epoxy treatment"). Through the epoxy treatment, acids in the impurities contained in the crude organic phosphoric ester are masked by epoxy groups.

The epoxy compound may be any one of aliphatic compounds, aromatic compounds, alicyclic compounds and heterocyclic compounds having one or more epoxy group in its structure.

Examples of the aliphatic epoxy compounds include ethylene oxide, propylene oxide, butylene oxide, 3,4-epoxybutanol, polyethylene glycol diglycidyl ether (e.g., having epoxy equivalent of 200 or 400), sorbitol polyglycidyl ether, sorbitan polyglycidyl ether, polyglycerol polyglycidyl ether, pentaerythritol polyglycidyl ether, diglycerol polyglycidyl ether, glycerol polyglycidyl ether, trimethylolpropane polyglycidyl ether, propylene glycol diglycidyl ether, polytetramethylene glycol diglycidyl ether, allyl glycidyl ether, 2-ethylhexyl glycidyl ether, adipic acid diglycidyl ester, dibromoneopentylglycol diglycidyl ether and the like.

Examples of the alicyclic epoxy compounds include 1-methyl-1,4-epoxycycloheptane, 2,3-epoxycyclopentanone, 3,4-epoxycyclooctene, 2,3-epoxynorbornane, 2-(3,4-

epoxycyclohexyl)-1,3-dioxolane, 4,5-epoxy-1-p-benzene, 1,2-epoxy-4-p-benzene, 1-(glycidylloxymethyl)-3,4-epoxycyclohexane, 2,3-epoxy-3,5,5-trimethylcyclohexanone, bis(2,3-epoxycyclopentyl)ether and the like.

5 Examples of the aromatic, heterocyclic and other epoxy compounds include phenyl glycidyl ether, p-tert-butylphenyl glycidyl ether, triglycidyl tris(2-hydroxyethyl)isocyanurate, o-phthalic acid diglycidyl ether, hydroquinone diglycidyl ether, terephthalic acid diglycidyl ether, glycidyl phthalimide,
10 dibromophenyl glycidyl ether, bisphenol A diglycidyl ether, bisphenol S diglycidyl ether and bisphenol F diglycidyl ether, as well as addition reaction products thereof.

 Among the above-described epoxy compounds, aliphatic epoxy compounds in a liquid state are preferable in
15 view of their excellent safety and easy availability. Propylene oxide and butylene oxide are particularly preferable.

 Reaction conditions of the epoxy treatment are not particularly limited and suitably selected depending on the physical properties and reactivities of the organic phosphoric
20 ester and the epoxy compound. However, it is preferred to dehydrate the crude organic phosphoric ester in advance because the epoxy group reacts with water.

 Where ethylene oxide in a gaseous state is used, for example, the treatment may be carried out by blowing ethylene
25 oxide into the crude organic phosphoric ester through an

insertion tube.

Where propylene oxide in a liquid state is used, the treatment may be carried out while adding propylene oxide dropwise to the crude organic phosphoric ester or after
5 propylene oxide is added to the crude organic phosphoric ester.

In the case of treating the organic phosphoric esters of the general formula (II) with propylene oxide or butylene oxide, the treatment temperature is preferably about 40 to 160°C, more preferably about 80 to 140°C, in view of their boiling points and
10 reactivities.

The treatment temperature lower than 40°C is not preferable because the treatment takes a long time. On the other hand, the treatment temperature higher than 160°C is not preferable because the organic phosphoric ester may be colored
15 or vigorous boiling may occur during the treatment.

The treatment is sufficiently carried out for a treatment time of about 0.5 to 2 hours. For example, the organic phosphoric esters of the general formula (II) are treated in about 0.5 hour with propylene oxide, and about 1 hour with butylene
20 oxide.

In theory, the epoxy compound is used in an amount corresponding to the acid value of the organic phosphoric ester. However, it is preferred to use the epoxy compound in an amount slightly greater than the amount corresponding to the acid value
25 of the organic phosphoric ester in view of reactivity of the epoxy

compound and loss by volatilization of a low boiling point epoxy compound, if used.

In general, the ratio between the crude organic phosphoric ester and the epoxy compound is preferably about 1:1 to 1:20 (molar ratio), more preferably about 1:2 to 1:5 (molar ratio) on the basis of the acid value of the crude organic phosphoric ester.

Then, the epoxy-treated organic phosphoric ester is treated with an alkaline aqueous solution (hereinafter this is referred to as an "alkali treatment"). Prior to the alkali treatment, the epoxy-treated organic phosphoric ester is preferably subjected to treatment with water or an acidic aqueous solution (preferably with water). This is called hereinafter an "intermediate treatment". The acidic aqueous solution may be an aqueous solution of hydrogen chloride or phosphoric acid in a concentration of about 0.01 to 1 wt%.

Through the intermediate treatment, acids in the impurities masked with the epoxy compound are hydrolyzed, which improves the efficiency of removing the impurities in the following alkali treatment.

Water or the acidic aqueous solution may be used in an amount of about 0.1 to 5 wt%, preferably about 0.2 to 2 wt% with respect to the crude organic phosphoric ester. The treatment is generally carried out once, but may be repeated as needed.

Specifically, for example, the epoxy-treated organic

phosphoric ester is added with water or the acidic aqueous solution, stirred for about 5 minutes to 3 hours, and if necessary, allowed to stand to separate an aqueous phase and an oily phase, and then the aqueous phase is removed.

5 To the organic phosphoric ester that has gone through the epoxy treatment, which may further be subjected to the intermediate treatment, an alkaline aqueous solution is added. According to the alkali treatment, acids in the impurities masked with the epoxy groups through the epoxy treatment are
10 converted to water-soluble compounds.

The alkaline aqueous solution is not particularly limited as long as it does not inhibit the purification of the organic phosphoric esters. In the present invention, alkali signifies a pH value ranging from about 8 to 13. Examples of
15 the alkaline aqueous solution include, for example, an aqueous solution of alkali metal carbonate such as sodium carbonate and potassium carbonate, alkali metal hydrogencarbonate such as sodium hydrogencarbonate and potassium hydrogencarbonate, alkali metal hydroxide such as sodium hydroxide and potassium
20 hydroxide. Among them, an aqueous solution of alkali metal carbonate is preferable and an aqueous solution of sodium carbonate is particularly preferable.

An alkali compound is used in the alkaline aqueous solution in an amount of 0.1 to 50 molar equivalent, preferably 1
25 to 5 molar equivalent, with respect to the acid value of the crude

organic phosphoric ester before the epoxy treatment.

The alkaline aqueous solution containing the alkali compound in an amount smaller than 0.1 molar equivalent with respect to the acid value of the crude organic phosphoric ester is not preferable because the organic phosphoric ester is not purified sufficiently. Further, the alkaline aqueous solution containing the alkali compound in an amount greater than 50 molar equivalent is not preferable because the removal of the alkali compound will be difficult and emulsification occurs to have influence on the separation.

The concentration of the alkaline aqueous solution is about 0.01 to 10 wt %, preferably about 0.1 to 1 wt %. The alkaline aqueous solution is used in an amount of about 1 to 100 wt %, preferably about 10 to 50 wt %, with respect to the crude organic phosphoric ester, from the calculation based on the above-mentioned amount of the alkali compound.

The treatment temperature is in the range of 60 to 120°C, preferably in the range of 70 to 95°C. At the treatment temperature within the range of 60 to 120°C, alkalis introduced in the treatment system hydrolyze the impurities efficiently without hydrolyzing the organic phosphoric ester.

The treatment time is appropriately determined depending on the treatment temperature. At the treatment temperature in the range of 60 to 120°C, the treatment is carried out sufficiently in about 0.5 to 2 hours. The higher the

treatment temperature is, the faster the treatment is completed.

The mixture solution containing the alkali-treated organic phosphoric ester is allowed to stand in order to remove the impurities that have been converted to the water-soluble compounds through the alkali treatment as an aqueous phase. Remaining alkalis are further reduced by washing with water as required. The washing treatment is carried out in the same manner as the above-mentioned intermediate treatment using water performed in advance of the alkali treatment.

Thus, the water-soluble impurities that cause a bad influence on the heat resistance, hydrolytic resistance and storage stability are removed.

Subsequently, water remaining in the organic phosphoric ester is removed, thereby obtaining the purified organic phosphoric ester.

Water may be removed by any one of processes commonly utilized in the art, but evaporation under reduced pressure is preferable. The evaporation under reduced pressure may remove, together with water, a solvent used to dissolve a solid crude organic phosphoric ester and a remaining organic solvent used to synthesize the crude organic phosphoric ester. However, it is preferred that the organic phosphoric ester is dehydrated, dried and subjected to steam distillation to remove such solvents.

Even in the case where the above-mentioned solvents

are not used, it is preferred to perform the steam distillation after the removal of water. Accordingly, low boiling point impurities that are hardly soluble to water (e.g., phenol as a synthesis material) are removed.

5 According to the purification method of the present invention, the organic impurities that are thermally unstable are completely converted to water soluble substances by hydrolysis and then removed. Therefore, excellent purification effect is attained.

10 According to the purification method of the present invention, the treatment is carried out at relatively low temperature. Therefore, side reactions during the treatment are inhibited and the reduction of the acid value of the organic phosphoric ester is not hindered.

15 Further, in an industrial view, thermal energy required for heating and time required for heating or cooling can be reduced, so that the organic phosphoric ester having a low acid value is obtained economically and conveniently.

20 Still according to the purification method of the present invention, the reduction of the acid value of the organic phosphoric ester is not hindered by the amount of the organic phosphoric ester to be treated. Therefore, it is particularly advantageous to the use in an industrial scale.

25 The "industrial scale" herein signifies that the organic phosphoric ester to be treated is used in an amount generally

employed in the industrial scale. Specifically, the amount of the organic phosphoric ester is 500 liter or greater, preferably 1000 liter or greater, more preferably 3000 liter or greater. The upper limit is not particularly established, but may be 30,000
5 liter or smaller, preferably 20,000 liter or smaller, more preferably 10,000 liter or smaller, due to the restriction by the reaction apparatus.

The organic phosphoric ester obtained by the purification method according to the present invention may be
10 used as a flame retardant for thermoplastic resins such as polyethylene based resins, polypropylene based resins, polybutadiene based resins, polystyrene based resins, polyphenyleneether based resins, polycarbonate based resins, acrylonitrile-butadiene-styrene (ABS) based resins, high impact
15 styrene based resins, acrylonitrile-styrene (SAN) based resins, polyamide based resins, polyester based resins, polyphenylenesulfide based resins and polyacryl based resins, and thermosetting resins such as epoxy based resins, polyurethane based resins, polyimide based resins, phenol
20 based resins, novolac based resins, polyetherimide based resins, melamine based resins and urea resins.

Since the organic phosphoric ester obtained by the method of the present invention has a low acid value, it is not decomposed even at a high treatment temperature during resin
25 molding. Accordingly, a high quality resin mold product having

high resistance to heat and discoloration is obtained.

The above-mentioned resin mold product can be obtained by a known method, e.g., by mixing and melt-kneading a flame retardant, a resin and, if necessary, other additives for the resin by using a single-screw extruder, a twin-screw extruder, a Banbury mixer, a kneading mixer, a roller and the like singly or in combination, and molding the obtained resin composition into the form of a plate, a sheet or a film by using a known molding apparatus.


Examples

The present invention will be described in further detail by way of the following preparation and examples, but they do not limit the scope of the present invention.

Preparation

Phosphorus oxychloride of 10,907 kg and bisphenol A of 3,000 kg were reacted in the presence of magnesium chloride of 30 kg as a catalyst under atmospheric pressure. An excess of phosphorus oxychloride was removed under reduced pressure, and then phenol of 4,932 kg was added and the reaction was maintained under reduced pressure until a theoretical amount of hydrogen chloride was generated. The thus obtained reaction mixture of 9,000 kg was added with toluene of 2,000 kg, and then 7.7 % phosphorus acid of 440 kg was added and stirred

at 85°C for 1 hour to remove the catalyst. Further, water of 2,000 kg at about 70°C was added and allowed to stand to separate an oily phase. The oily phase was dehydrated under reduced pressure to obtain a crude reaction product of 11,000 kg mainly comprised of bis(diphenyl phosphate)bisphenol A as represented by the following formula. The crude reaction product was a transparent, colorless and viscous liquid having an acid value of 1.2 and water content of 150 ppm.



Example

To the crude reaction product of 11.0 t obtained in the above preparation, butylene oxide of 85 kg was added (molar ratio between the crude reaction product and butylene oxide was 1:5 based on the acid value of the crude reaction product) and they were reacted at 120°C for 2 hours (epoxy treatment).

Then, the reaction mixture was cooled to 85°C, water of 73 kg (0.66 wt% with respect to the crude reaction product) was added thereto and stirred for 2 hours (intermediate treatment).

Further, 0.8 wt% aqueous sodium carbonate solution of 3,000 kg (27.3 wt% with respect to the crude reaction product) was added and stirred at 85°C for 15 minutes (alkali treatment), and then allowed to stand to separate an oily phase.

204210-121000T
The separated oily phase was washed twice with water of 3,100 kg at about 70°C and subjected to steam distillation at 140°C /50 mmHg for 7 hours to remove impurities such as remaining phenol, thereby obtaining a purified product of about
5 8.8 t (yield: 97.5 % ca.)

The obtained purified product showed the acid value of 0.014 and Na content of 0.7 ppm. Hue based on Hazen's color number method was 25 and purity obtained by gel permeation chromatography (GPC) was 85.4%.

10 The obtained purified product of 150 g was subjected to a heat resistant test at 250°C for 3 hours. After the test, the acid value was 0.25, hue based on Gardner's color number method was 1 and purity was 84.9 %.

15 Comparative Example 1

To a crude reaction product of 11.0 t obtained in the same manner as in the above preparation, butylene oxide of 85 kg was added (molar ratio between the crude reaction product and butylene oxide was 1:5 based on the acid value of the crude
20 reaction product) and they were reacted at 120°C for 2 hours (epoxy treatment).

Then, the reaction mixture was cooled to 85°C, water of 73 kg (0.66 wt% with respect to the crude reaction product) was added and stirred for 2 hours (intermediate treatment).

25 Subsequently, water of 310 kg at about 85°C was added

and stirred for 1 hour (thermal treatment), and then water of 2,000 kg at about 85°C was added to separate an oily phase.

The separated oily phase was washed twice with water of 3,100 kg at about 85°C and subjected to steam distillation at 140°C / 50 mmHg for 7 hours to remove impurities such as remaining phenol, thereby obtaining a purified product of about 8.8 t (yield: 97.5 % ca.)

The obtained purified product showed the acid value of 0.124 and the Na content of 0.6 ppm.

The results of Example and Comparative Example 1 indicate that the organic phosphoric ester purified by the method of the present invention shows, though it was treated in the industrial scale, a lower acid value and equivalent Na content as compared with those of an organic phosphoric ester purified by a conventional method.

The fact that the acid value is low signifies that impurities derived from phosphoric acid and chloride in the starting materials are reduced. Therefore, the organic phosphoric ester purified by the method of the present invention has physical properties that are close to inherent ones of the organic phosphoric ester and is excellent in heat resistance, hydrolytic resistance and storage stability. Further, since the Na content is small, the organic phosphoric ester purified by the method of the present invention is free from the problem of

discoloration.

Comparative Example 2 (Japanese Unexamined Patent
Publication No. Hei 8 (1996)-67685, Example 1)

5 To a crude reaction product of 11.0 t obtained in the
same manner as in the above preparation, propylene oxide of 68
kg was added (molar ratio between the crude reaction product
and propylene oxide was 1:5 based on the acid value of the crude
reaction product) and they were reacted at 120°C for 2 hours
10 (epoxy treatment).

Then, the reaction product was cooled to 85°C and
washed with water of 3,100 kg at 85°C (intermediate treatment).

Then, it was stirred at 140°C for 30 minutes (thermal
treatment), and allowed to stand to separate an oily phase.

15 The separated oily phase was washed with water of
3,100 kg at about 85°C, moisture was removed by distillation
under reduced pressure, and further subjected to steam
distillation at 140°C /50 mmHg for 4 hours to remove impurities
such as remaining phenol, thereby obtaining a purified product
20 of about 8.8 t (yield: 97.5 % ca.).

The obtained purified product showed the acid value of
0.09 and the Na content of 0.6 ppm. Hue based on Hazen's
color number method was 30 and purity obtained by GPC was
85.35 %.

25 The obtained purified product of 150 g was subjected to

a heat resistant test at 250°C for 3 hours. After the test, the acid value was 0.69, hue based on Gardner's color number method was 3 and purity was 82.9 %.

5 The results of Example and Comparative Example 2 are shown in Table 1.

Table 1

	Example		Comparative Example 2	
	Before heat resistant test	After heat resistant test	Before heat resistant test	After heat resistant test
Acid value	0.014	0.25	0.09	0.69
Hue	H-25	G-1	H-30	G-3
Purity	85.4%	84.9%	85.35%	82.9%

H and G stand for the hues based on Hazen's color number method and Gardner's color number method, respectively.

10

Table 1 indicates that the organic phosphoric ester purified by the method of the present invention shows higher heat resistance than that of an organic phosphoric ester purified by a conventional method, even if it was treated in the industrial scale.

15

The purification method according to the present invention does not require any operations for establishing complicated conditions that have been conducted in the

conventional method. Further, by a simple treatment using an alkaline aqueous solution, the impurities that cause a bad influence on the physical properties such as heat resistance, hydrolytic resistance and storage stability can be removed.

- 5 Moreover, even if the alkali metal compound, which may cause discoloration of the organic phosphoric ester, is used during the treatment, it is hardly left after the treatment and thus the problem of the discoloration is eliminated.

- 10 Further, according to the purification method of the present invention, the organic phosphoric ester even in an amount in the industrial scale can be treated.

The organic phosphoric ester purified by the method of the present invention has a low acid value and is excellent in heat resistance, hydrolytic resistance and storage stability.

- 15 Therefore, even if it is added to a resin as a plasticizer or a flame retardant, it maintains stability at a molding temperature of the resin and thus does not cause any change in composition.

CLAIMS

1. A method of purifying an organic phosphoric ester characterized in that the purification is carried out by treating a
5 crude organic phosphoric ester with an epoxy compound and treating the treated organic phosphoric ester with an alkaline aqueous solution.
2. A method according to claim 1, wherein the epoxy
10 compound is propylene oxide or butylene oxide.
3. A method according to claim 1 or 2, wherein the ratio between the crude organic phosphoric ester and the epoxy
15 compound is 1:1 to 1:20 (molar ratio) based on an acid value of the crude organic phosphoric ester.
4. A method according to any one of claims 1 to 3, wherein the treatment with the epoxy compound is carried out at 40 to
20 160°C.
5. A method according to any one of claims 1 to 4, wherein the organic phosphoric ester that has been treated with the epoxy compound is treated with water or an acidic aqueous
25 solution in advance of the treatment with the alkaline aqueous solution.

6. A method according to any one of claims 1 to 5, wherein the alkaline aqueous solution is an aqueous solution of an alkali metal carbonate.

5

7. A method according to claim 6, wherein the aqueous solution of alkali metal carbonate is an aqueous solution of sodium carbonate.

10 8. A method according to any one of claims 1 to 7, wherein an amount of an alkali compound in the alkaline aqueous solution is 0.1 to 50 molar equivalent with respect to the acid value of the crude organic phosphoric ester which is not yet treated with the epoxy compound.

15

9. A method according to any one of claims 1 to 8, wherein a concentration of the alkaline aqueous solution is 0.01 to 10 wt%.

20 10. A method according to any one of claims 1 to 9, wherein the treatment with the alkaline aqueous solution is carried out at 60 to 120°C.

11. A method according to any one of claims 1 to 10,
25 wherein the organic phosphoric ester is a compound represented

[illegible]

5

10

15

Declaration and Power of Attorney For Utility or Design Patent Application

特許出願宣言書

Japanese Language Declaration

私は、下欄に氏名を記載した発明者として、以下のとおり
宣言する：

私の住所、郵便の宛先および国籍は、下欄に氏名に続いて記載したとおり
であり、

名称の発明に関し、請求の範囲に記載した特許を求める主題の本来の、
最初にして唯一の発明者である(一人の氏名のみが下欄に記載されている
場合)か、もしくは本来の、最初にして共同の発明者である(複数の氏名が
下欄に記載されている場合)と信じ、

上記発明の明細書(下記の欄でX印がついていない場合は、
本書に添付)は、

____年____月____日に提出され、

米国出願番号 _____ とし、

(該当する場合) ____年____月____日に訂正されました。又は、

特許協定条約国際出願番号 _____ とし、

(該当する場合) ____年____月____日に訂正されました。

私は、前記のとおり補正した請求の範囲を含む前記明細書の内容を検討
し、理解したことを陳述する。

私は、連邦規則法典第37編第1条第56項に定義されるとおり、特許資
格の有無について重要な情報を開示すべき義務があることを認めます。

私は合衆国法典第35部第119条(a-d)項又は第365条(b)項に基づく、下
記の外国特許出願又は発明者証出願、或いは第365条(a)項に基づく、少な
くとも米国以外の1ヶ国を指名したPCT国際出願の外国優先権を主張し、
更に優先権の主張に係わる基礎出願の出願日前の出願日を有する外国特許
出願、又は発明者証出願或るいはPCT国際出願を以下に“なし”の箱に印を
つけることにより明記する：

Prior foreign applications
先の外国出願

Hei 11(1999)-231704	JAPAN	18/08/1999
(Number)	(Country)	(Day/Month/Year Filed)
(番号)	(国名)	(出願の年月日)
_____	_____	_____
(Number)	(Country)	(Day/Month/Year Filed)
(番号)	(国名)	(出願の年月日)

☐ その他の外国特許出願番号は別紙の追補優先権欄にて記載する。

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated
below next to my name.

I believe I am the original, first and sole inventor (if only one name is
listed below) or an original, first and joint inventor (if plural names
are listed below) of the subject matter which is claimed and for
which a patent is sought on the invention entitled

Method of Purifying Organic Phosphoric Ester

the specification of which is attached hereto unless the following
box is checked:

☐ was filed on _____ as

United States Application Number _____

and was amended on _____ (if applicable) or,

PCT International Application Number _____

and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents
of the above identified specification, including the claims, as
amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to
patentability as defined in Title 37, Code of Federal Regulations,
§1.56.

I hereby claim foreign priority under Title 35, United States Code
§119(a-d) or §365(b) of any foreign application(s) for patent or
inventor's certificate, or §365(a) of any PCT international application
which designated at least one country other than the United States,
listed below. I have also identified below, by checking the "No"
box, any foreign application for patent or inventor's certificate, or of
any PCT international application having a filing date before that of
the application on which priority is claimed:

Priority claimed

優先権の主張

<input checked="" type="checkbox"/>	<input type="checkbox"/>
Yes	No
あり	なし
<input type="checkbox"/>	<input type="checkbox"/>
Yes	No
あり	なし

☐ Additional foreign application numbers are listed on a
supplemental priority sheet attached hereto.

Japanese Language Utility or Design Patent Application Declaration

私は、合衆国法典第35部第119条(e)項に基づく、下記の合衆国仮特許出願の利益を主張する。

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States provisional application(s) listed below.

(Application No.)
(出願番号)

(Day/Month/Year Filed)
出願の年月日

(Application No.)
(出願番号)

(Day/Month/Year Filed)
出願の年月日

(Application No.)
(出願番号)

(Day/Month/Year Filed)
出願の年月日

☐ その他の合衆国仮特許出願番号は別紙の追補優先権欄にて記載する。

☐ Additional provisional application numbers are listed on a supplemental priority sheet attached hereto.

私は、合衆国法典第35部第120条に基づく下記の合衆国特許出願、又は第365条(c)項に基づく合衆国を指名したPCT国際出願の利益を主張し、本願の請求の範囲各項に記載の主題が合衆国法典第35部第112条第1項規定の態様で、先の合衆国特許出願又はPCT国際出願に開示されていない限度において、先の出願の出願日と本願の国内出願日又はPCT国際出願日の間に有効となった連邦規則法典第37部第1章第56条に記載の特許要件に所要の情報を開示すべき義務を有することを認める。

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s), or §365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations §1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

PCT/JP00/04003

(Application No.)
(出願番号)

19/06/2000

(Day/Month/Year Filed)
(出願の年月日)

Pending

(現況)
(特許済み、係属中 放棄済み)

(Status)
(patented, pending, abandoned)

(Application No.)
(出願番号)

(Day/Month/Year Filed)
(出願の年月日)

(現況)
(特許済み、係属中 放棄済み)

(Status)
(patented, pending, abandoned)

☐ その他の合衆国又は国際特許出願番号は別紙の追補優先権欄にて記載する。

☐ Additional U.S. or international application numbers are listed on a supplemental priority sheet attached hereto.

私は、ここに自己の知識にもとずいて行った陳述がすべて真実であり、自己の有する情報および信ずるところに従って行った陳述が真実であると信じ、さらに故意に虚偽の陳述等を行った場合、合衆国法典第18部第1001条により、罰金もしくは禁錮に処せられるか、またはこれらの刑が併科され、またかかる故意による虚偽による陳述が本願ないし本願に対して付与される特許の有効性を損なうことがあることを認識して、以上の陳述を行ったことを宣言する。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

私、下記署名者は、ここに記載の米国弁護士または代理人に本出願に関し特許商標庁にて取られるいかなる行為に関して、同米国弁護士又は代理人が、私に直接連絡なしに私の外国弁護士或いは法人代表者からの指示を受け取り、それに従うようここに委任する。この指示を出す者が変更の場合には、ここに記載の米国弁護士又は代理人にその旨通知される。

The undersigned hereby authorizes the U.S. attorney or agent named herein to accept and follow instructions from either his foreign patent agent or corporate representative, if any, as to any action to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorney or agent and the undersigned. In the event of a change in the persons from whom instructions may be taken, the U.S. attorney or agent named herein will be so notified by the undersigned.

Japanese Language Utility or Design Patent Application Declaration

委任状： 私は、下記発明者として、下記に明記された顧客番号を伴う以下の弁護士又は、代理人をここに選任し、本願の手続きを遂行すること並びにこれに関する一切の行為を特許商標庁に対して行うことを委任する。そして全ての通信はこの顧客番号宛に発送される。

顧客番号 7055

現在選任された弁護士は下記の通りである。

POWER OF ATTORNEY: As a named inventor, I hereby appoint the attorney(s) and/or agent(s) associated with the Customer Number provided below to prosecute this application and transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to that Customer Number:

CUSTOMER NUMBER 7055

The appointed attorneys presently include:

Neil F. Greenblum Reg. No. 28,394
Bruce H. Bernstein Reg. No. 29,023
James L. Rowland Reg. No. 32,674
Arnold Turk Reg. No. 33,094

Address: **GREENBLUM & BERNSTEIN, P.L.C.**

1941 ROLAND CLARKE PLACE
RESTON, VA 20191

直接電話連絡先：(名称および電話番号)

Direct Telephone Calls to: (name and telephone number)

GREENBLUM & BERNSTEIN, P.L.C.

(703) 716-1191

唯一のまたは第一の発明者の氏名	1-00	Full name of sole or first inventor	Kiyocharu HIRAO
同発明者の署名	日付	Inventor's signature	K. Hiraio 26/12/2001
住所		Residence	Sennan, JAPAN
国籍		Citizenship	JAPAN JPX
郵便の宛先		Post Office Address	2-10-4, Kibougaoka, Kumatori-cho, Sennan-gun, Osaka 590-0422 JAPAN
第2の共同発明者の氏名 (該当する場合)	2-00	Full name of second joint inventor, if any	Masasuke ODA
同第2共同発明者の署名	日付	Second inventor's signature	M. Oda 26/12/2001
住所		Residence	Ashiya, JAPAN
国籍		Citizenship	JAPAN JPX
郵便の宛先		Post Office Address	9-17, Midori-cho, Ashiya-shi, Hyogo 659-0042 JAPAN

(第六またはそれ以降の共同発明者に対しても同様な情報および署名を提供すること。)

(Supply similar information and signature for third and subsequent joint inventors.)

GREENBLUM & BERNSTEIN, P.L.C.
INTELLECTUAL PROPERTY CAUSES
1941 ROLAND CLARKE PLACE
RESTON, VA 20191

Applicant or Patentee: DAIHACHI CHEMICAL INDUSTRY CO., LTD. Attorney's
Serial or Patent No: _____ Docket No.: _____
Filed or Issued: _____
For: _____

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
STATUS (37 CFR 1.9 (f) and 1.27(c)) - SMALL BUSINESS CONCERN

I hereby declare that I am

- ☐ the owner of the small business concern identified below:
☒ an official of the small business concern empowered to act on behalf of the concern identified below:

NAME OF SMALL BUSINESS CONCERN DAIHACHI CHEMICAL INDUSTRY CO., LTD.
ADDRESS OF SMALL BUSINESS CONCERN Hiranomachi Yachiyo Bldg., 8-13, Hiranomachi
1-chome, Chu-ku, Osaka-shi, Osaka 541-0046 JAPAN

I hereby declare that the above identified small business concern qualifies as a small business concern as defined in 13 CFR 121.12, and reproduced in 37 CFR 1.9(d), for purposes of paying reduced fees to the United States Patent and Trademark Office, in that the number of employees of the concern, including those of its affiliates, does not exceed 500 persons. For purposes of this statement, (1) the number of employees of the business concern is the average over the previous fiscal year of the concern of the persons employed on a full-time, part-time or temporary basis during each of the pay periods of the fiscal year, and (2) concerns are affiliates of each other when either, directly or indirectly, one concern controls or has the power to control the other, or a third party or parties controls or has the power to control both.

I hereby declare that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention, entitled Method of Purifying Organic by inventor(s) Kiyocharu HIRAO and Masasuke ODA described in Phosphoric Ester

- ☒ the specification filed herewith
☐ application serial no. _____, filed _____
☐ patent no. _____, issued _____

If the rights held by the above identified small business concern are not exclusive, each individual, concern or organization having rights in the invention is listed below* and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e) *NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

FULL NAME _____

ADDRESS _____

☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

FULL NAME _____

ADDRESS _____

☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28 (b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

NAME OF PERSON SIGNING Hitoshi YOSHIKAWA

TITLE OF PERSON IF OTHER THAN OWNER President

ADDRESS OF PERSON SIGNING 2-1220-26, Maniyama, Nara-shi, Nara 631-0056 JAPAN

SIGNATURE Hitoshi Yoshikawa DATE 21 / 12 / 2001

Hitoshi YOSHIKAWA

December 21, 2001